



Fall protection

AN245200CDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN355

Protects against risks



Fall



Fall protection

AN245200CDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
Color	Black-Orange
Connector (user side)	Screw carabiner, steel, opening 18mm
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



Fall protection

AN245200CDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
-----------	--------	------	-------------	-------	----------	---	---	--------	---	---	---

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height