



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system



Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Mining

Certifications and norms



EN358

Protects against risks



Fall



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system

Standards - Details

Technical details

Type of equipment	Work positioning system
Composition of the main support	Polyamide
Max. length (m)	2
Min. length (m)	0,20
Length (m)	2
Rope diameter (mm)	10,5
With connector	yes
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
Connector (structure side)	Small hook, steel, opening 21 mm
Fall arrest work situations	Work positioning, Restraint
Lenght (ft)	6.5616



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS0002AC011 [EX030200]	White	0.20 → 2 m	EX030200	3660348005166	13660348005163	5	1	6.35 kg	27.0 cm	47.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height