



Fall protection

AN217200ADD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard, tested on sharp edges guaranteeing freedom of movement for short distances



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg



Easy to use

- NFC system guarantees traceability

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Protects against risks



Fall



Fall protection

AN217200ADD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard, tested on sharp edges guaranteeing freedom of movement for short distances

Standards - Details

Technical details

Type of equipment	Braided rope lanyard with energy absorber
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Rope diameter (mm)	12
With connector	yes
Color	White-Black
Connector (user side)	Automatic lock hook, steel, opening 19mm
Benefits element	Leading edge
Ending	3 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,7
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



Fall protection

AN217200ADD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard, tested on sharp edges guaranteeing freedom of movement for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAD3002DZ011 [AN217200ADD]	White-Black	2 m	AN217200ADD	3295249313753	13295249313750	5	1	9.7 kg	28.0 cm	44.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height