手部防护

VE530V2

长期耐化学风险作业

化学手套，兼具舒适性和灵活性，是食品工业的理想选择



具体优势

高性能

· 额外加厚加长设计，提供全臂防护

兼容性

· 适用于食品行业

应用行业

- 石油化工
- 清洁

标准和认证

CE 3类

EN 388
3 1 1 0 X

EN ISO 374-1
种类 A
AKLMNPST

EN ISO 374-5
VIRUS

防范风险

化学

DELTAPLUS

enjoy safety

编辑 04/11/2026
www.deltaplus.com.cn

手部防护

VE530V2

长期耐化学风险作业

化学手套，兼具舒适性和灵活性，是食品工业的理想选择

详细信息 - 标准

EN388:2016+A1:2018
3 [0-4] 耐磨
1 [0-5] 防切割
1 [0-4] TEAR RESISTANCE
0 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

EN 374
A : MÉTHANOL
K
L
M
N
P
S
T

技术细节

手套类别	贴手的手套
手套类别	无粉无基布紧手套
贴手的手套类别	无支撑
涂层水平	全涂层
涂层材质	乳胶, 氯丁橡胶
涂层饰面	抓纹涂层
涂层数	单涂层
内部处理	植绒
厚度 (mm)	0,70
手臂保护	前臂袖口 (< 400mm)
颜色	黑色
尺码	6, 7, 8, 9, 10
包装类型	独立包装

包装

销售单位: 独立包装
120 成对/箱

VE530V2

长期耐化学风险作业

手部防护

化学手套，兼具舒适性和灵活性，是食品工业的理想选择

渗透表

化学品	信件	CAS #	渗透水平	渗透时间（分钟）	中等退化
Methanol	A	67-56-1	2	30	15.5%
Sodium hydroxide 40%	K	1310-73-2	6	480	-6.8%
Sulphuric acid 96 %	L	7664-93-9	4	120	21.0%
Nitric acid 65%	M	7697-37-2	6	480	18.4%
Acetic acid 99%	N	64-19-7	3	60	23.4%
Hydrogen peroxide 30%	P	7722-84-1	6	480	3.4%
Hydrofluoric acid 40%	S	7664-39-3	6	480	X
Formaldehyde 37%	T	50-00-0	6	480	8.1%

Safety gloves

VE530V2

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove, combining comfort and flexibility, ideal for the food industry

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
GWE530C102BK 06 [VE530V206]	Black	06	VE530V2	3295249315252	13295249315259	120	12	14.0 kg	29.6 cm	44.8 cm	32.0 cm
GWE530C102BK 07 [VE530V207]	Black	07	VE530V2	3295249315269	13295249315266	120	12	16.0 kg	29.6 cm	44.8 cm	32.0 cm
GWE530C102BK 08 [VE530V208]	Black	08	VE530V2	3295249315276	13295249315273	120	12	16.0 kg	29.6 cm	44.8 cm	32.0 cm
GWE530C102BK 09 [VE530V209]	Black	09	VE530V2	3295249315283	13295249315280	120	12	16.5 kg	29.6 cm	44.8 cm	32.0 cm
GWE530C102BK 10 [VE530V210]	Black	10	VE530V2	3295249315290	13295249315297	120	12	17.0 kg	29.6 cm	44.8 cm	32.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height