



Hand protection

APOLLON WINTER VV735 Fluorescent Yellow-Black

THERMAL COLD WORKS

Thermal glove ideal for mild cold environments



Specific benefits



Performance

- Lightweight for optimal dexterity
- Excellent resistance to cold and humidity, ideal for cold environments down to -30°C

Applications

- Agriculture
- Public Works
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Temporary Work

Certifications and norms



EN 388
1 1 3 2 X



EN 511
X
1
X

Risk Protection



Cold



Hand protection

APOLLON WINTER VV735 Fluorescent Yellow-Black

THERMAL COLD WORKS

Thermal glove ideal for mild cold environments

Standards - Details



EN388:2016+A1:2018

- 1 [0-4] ABRASION RESISTANCE
- 1 [0-5] CUT RESISTANCE
- 3 [0-4] TEAR RESISTANCE
- 2 [0-4] PIERCE RESISTANCE
- X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Special glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Special gloves kind	Cold
Coating material and finition	Nitrile foam
Coating Level	Palm Coating
Number of Coatings	Single Coated
Gauge	10
Benefits element	High-Viz, Reach, Vendor pack, Azo Free
Color	Fluorescent Yellow-Black
Size	9, 10
Type of conditioning	in individual bags








Safety gloves

APOLLON WINTER VV735

THERMAL COLD WORKS

Thermal glove ideal for mild cold environments

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
VV735JA09	Fluorescent Yellow-Black	09	APOLLON WINTER VV735	3295249178277	13295249178274	60	12	7.308 kg	28.2 cm	64.2 cm	21.8 cm
VV735JA10	Fluorescent Yellow-Black	10	APOLLON WINTER VV735	3295249178284	13295249178281	60	12	7.6 kg	23.0 cm	61.8 cm	29.0 cm
VV735GR09	Gray-Black	09	APOLLON WINTER VV735	3295249180539	13295249180536	60	12	6.9 kg	28.8 cm	62.0 cm	23.4 cm
VV735GR10	Gray-Black	10	APOLLON WINTER VV735	3295249180546	13295249180543	60	12	7.1 kg	28.8 cm	63.0 cm	22.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height