Hand protection

VE509

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove with good grip for all types of applications



Specific benefits

Performance

· Extra thick and long for extra protection of the entire arm

Applications

- **Public Works**
- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Chemical Industry**
- **Automotive**

Certifications and norms

CE CATEGORY III

EN 388
3 1 1 0 X

EN ISO 374-1
TYPE A
AKLMNOPT

EN ISO 374-5

Risk Protection

Biological | Wearing | Chemical | Particules

DELTAPLUS

enjoy safety.

Edit 15/11/2026
www.deltaplus-usa.com

Hand protection

VE509

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove with good grip for all types of applications

Standards - Details

EN388:2016+A1:2018
3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
1 [0-4] TEAR RESISTANCE
0 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

EN 374
A : MÉTHANOL
K
L
M
N
O
P
T

Technical details

Glove kind	Tight glove
Glove family	Tight glove supported
Tight glove kind	Supported
Coating Level	Full Coating
Coating Material	Neoprene
Coating Finish	Grip-textured
Number of Coatings	Single Coated
Inner finition	Flocked
Lining material	Cotton Textile
Thickness (mm)	0,75
Arm level protection	Forearm cuff (< 400mm)
Benefits element	Reach
Color	Black
Size	6, 7, 8, 9, 10, 11
Type of conditioning	in individual bag

Packaging

Sale unit: in individual bag
120 pairs /box

Hand protection

VE509

WORK WITH PROLONGED CHEMICAL RESISTANCE

Chemical glove with good grip for all types of applications

Permeation table

Chemicals	Letter	CAS #	Permeation level	Permeation time (minutes)	Dégradation moyenne
Methanol	A	67-56-1	3	60	3.8%
Sodium Hydroxyde 40%	K	1310-73-2	6	480	-0.1%
Acide Sulfurique 96%	L	7664-93-9	4	120	23.5%
Nitric Acid 65%	M	7697-37-2	6	480	19.3%
Acetic Acid 99%	N	64-19-7	5	240	19%
Hydroxyde d'ammonium 25%	O	1336-21-6	3	60	-12.9%
Peroxyde d'Hydrogène 30%	P	7722-84-1	6	480	-2.8%
Acide hydrofluorique 40%	S	7664-39-3	6	480	X
Formaldehyde 37%	T	50-00-0	6	480	6.7%

VE509

TRABALHOS PROLONGADOS COM RESISTÊNCIAS QUIMICAS

Proteção das mãos

Luva química com uma boa aderência aos objetos manuseados para todos os tipos de aplicações

Informação logística

Referência	Cor	Tamanho	Designação	EAN 13	Código da caixa			Peso			
GWE509C101BK07 [VE509NO06]	Preto	6/7	VE509	3295249011970	13295249011977	120	12	17.0 kg	27.5 cm	30.0 cm	61.0 cm
GWE509C101BK08 [VE509NO07]	Preto	7/8	VE509	3295249011987	13295249011984	120	12	13.5 kg	27.5 cm	30.0 cm	61.0 cm
GWE509C101BK09 [VE509NO08]	Preto	8/9	VE509	3295249011994	13295249011991	120	12	15.0 kg	27.5 cm	30.0 cm	61.0 cm
GWE509C101BK10 [VE509NO09]	Preto	9/10	VE509	3295249012007	13295249012004	120	12	16.0 kg	27.5 cm	30.0 cm	61.0 cm
GWE509C101BK11 [VE509NO10]	Preto	10/11	VE509	3295249012014	13295249012011	120	12	17.2 kg	27.5 cm	30.0 cm	61.0 cm

Caixa completa

Mínimo venda

Largura da caixa

Profundidade da caixa

Altura da caixa