



Fall protection

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances



Specific benefits



Performance

- Certification above maximum rated load 100kg; product certified at 150kg



Ease of Use

- NFC system guarantees traceability



Visibility

- Anti-fall visual indicator allows for instant verification that product is properly functioning

Certifications and norms



150 KG
150 KG (MAXIMUM RATED LOAD)
50 KG (MINIMUM NOMINAL LOAD)
F0 | USE: VERTICAL

Applications

- Finishing Works/Craftsmanship
- Light Industry
- Temporary Work

Risk Protection



Fall



enjoy safety.

Edit 31/08/2026
www.deltaplus-usa.com



Fall protection

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	ABS, Steel, Polyester
Max. length (m)	2,5
Strap width (mm)	47
Min. length (m)	0,55
ARA lenght (m)	2,5
ARA lenght (inch)	98.4253
Fall factor	F0
Included elements	Energy absorber
Color	Black
Connector 1	Screw carabiner, steel, opening 18mm
Benefits element	Fall indicator
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.9
Maximum load for one person (kg)	150
Type of conditioning	Sold by Unit
Fall arrest work situations	Short vertical movement or movement on inclined surface (less than 3 m)
Locking system	Inertia locking system
Maximum rated load (kg)	150
Use of self retracting	Vertical



Fall protection

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
SRLMINS2Z501BK [AN101S25]	Black	2.50 m	MINIBLOC AN101S25	3295249323981	13295249323988	5	1	7.9 kg	59.5 cm	24.7 cm	16.3 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height