Fall protection

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances

Specific benefits

Performance

· Certification above maximum rated load 100kg: product certified at 150kg

Ease of Use

· NFC system guarantees traceability

Visibility

· Anti-fall visual indicator allows for instant verification that product is properly functioning

Certifications and norms

CE CATEGORY III

150 KG
150 KG (MAXIMUM RATED LOAD)
50 KG (MINIMUM NOMINAL LOAD)
F0 | USE: VERTICAL

Applications

- **Finishing Works/Craftsmanship**
- **Light Industry**
- **Temporary Work**

Risk Protection

Fall

Fall protection

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	Steel, Polyester
Max. length (m)	2,5
Strap width (mm)	47
Min. length (m)	0,55
ARA lenght (m)	2,5
ARA lenght (inch)	98.4253
Fall factor	F0
Included elements	Energy absorber
Color	Black
Connector 1	Screw carabiner, steel, opening 18mm
Benefits element	Fall indicator
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.9
Maximum load for one person (kg)	150
Type of conditioning	Sold by Unit
Fall arrest work situations	Short vertical movement or movement on inclined surface (less than 3 m)
Locking system	Inertia locking system
Maximum rated load (kg)	150
Use of self retracting	Vertical

MINIBLOC AN101S25

RETRACTABLE FALL ARRESTERS

Lightweight and compact webbing retractor for short distances

Fall protection

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
SRLMINS2Z501BK [AN101S25]	Black	2.50 m	MINIBLOC AN101S25	3295249323981	13295249323988	5	1	7.9 kg	0.22 m	0.585 m	0.14 m

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height