



Protection des mains

FCN29

TRAVAUX MILIEU SEC

Gant mécanique cuir, idéal pour travaux polyvalents en milieu sec



Applications

- Travaux publics
- Bâtiment
- Second œuvre / Artisans
- Travail temporaire
- Stockage

Certifications et normes



Protège contre les risques



Usure



Protection des mains

FCN29

TRAVAUX MILIEU SEC

Gant mécanique cuir, idéal pour travaux polyvalents en milieu sec

Détails - Normes



EN388:2016+A1:2018

2 [0-4] RÉSISTANCE À L'ABRASION
1 [0-5] RÉSISTANCE À LA COUPURE
2 [0-4] RÉSISTANCE À LA DÉCHIRURE
1 [0-4] RÉSISTANCE À LA PERFORATION
X [A-F] RÉSISTANCE À LA COUPURE SELON ISO 13997

Détails techniques

Type de gant	Gant mécanique
Famille de gants	Gant coupé cousu paume cuir / dos cuir
Type de gant mécanique	Coupé cousu
Epaisseur (mm)	0,9 -> 1,1
Caractéristique manchette	Manchette ouverte dos élastiqué
Couleur	Naturel
Tailles	8, 9, 10, 11
Type de conditionnement	Sachet vrac de 12

Conditionnement

Unité de vente: Sachet vrac de 12
120 paires /carton



Safety gloves

FCN29

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, ideal for multipurpose work in dry environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
GLFCN2UD01NA 10 [FCN2910]	Natural	10	FCN29	3295249028886	13295249028883	120	12	17.6 kg	28.6 cm	63.0 cm	30.8 cm
GLFCN2UD01NA 11 [FCN2911]	Natural	11	FCN29	3295249028893	13295249028890	120	12	18.5 kg	27.8 cm	63.6 cm	32.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height