



Hand protection

FCN29

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, ideal for multipurpose work in dry environments



Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Temporary Work
- Storage

Certifications and norms



EN 388
2121X

Risk Protection



Wearing



Hand protection

FCN29

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, ideal for multipurpose work in dry environments

Standards - Details



EN388:2016+A1:2018

2 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
1 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical Glove Type	Cut Sewn
Thickness (mm)	0,9 -> 1,1
Cuff characteristic	Sewn open cuff with elastic
Color	Natural
Size	8, 9, 10, 11
Type of conditioning	Bulk bag of 12








Safety gloves

FCN29


WORKS IN DRY ENVIRONMENT

Mechanical leather glove, ideal for multipurpose work in dry environments

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
FCN2910	Natural	10	FCN29	3295249028886	13295249028883	120	12	17.6 kg	28.6 cm	63.0 cm	30.8 cm
FCN2911	Natural	11	FCN29	3295249028893	13295249028890	120	12	18.5 kg	27.8 cm	63.6 cm	32.0 cm

 Multiple Sales

 Minimum Order Quantity

 Box Width

 Box Depth

 Box Height