



Hand protection

FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing



Specific benefits



Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- Agriculture
- Public Works
- Building
- Maintenance
- Cleanliness
- Temporary Work

Certifications and norms



EN 388

3 2 4 3 B



EN 407

4 1 X 1 X X

Risk Protection



Heat



Cutting



enjoy safety

Edit 19/03/2025
www.deltaplus-usa.com



Hand protection

FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
2 [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
3 [0-4] PIERCE RESISTANCE
B [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical Glove Type	Cut Sewn
Leather Treatment	Hydro
Thickness (mm)	1,0 -> 1,2
Cuff characteristic	Sewn open cuff with elastic
Benefits element	Repellent
Color	Beige
Size	8, 9, 10
Type of conditioning	Bulk bag of 12








Safety gloves

FIBKV02

WORKS IN WET ENVIRONMENT

Water-repellent mechanical leather glove with Kevlar lining for high durability, ideal for electric arcing

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
FIBKV0210	Beige	10	FIBKV02	3295249048532	13295249048539	60	12	4.0 kg	60.0 cm	28.0 cm	24.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height