Hand protection

EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Anti-impact glove with level B cut resistance, flexible and comfortable, ideal for heavy-duty work in dry conditions.



Certifications and norms

CE CATEGORY II

EN 388
3 X 4 2 B P

EN 407
X 2 X X X X

ANSI ISEA 138
LEVEL 1

Risk Protection

Heat | Shock | Cutting | Wearing

Specific benefits

Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)
· Flexible reinforcements for added protection against impact and pinching
· SOFTnocut fiber provides excellent cut resistance

Applications

- **Agriculture**
- **Public Works**
- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Automotive**

Hand protection

EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Anti-impact glove with level B cut resistance, flexible and comfortable, ideal for heavy-duty work in dry conditions.

Standards - Details

EN388:2016+A1:2018
3 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
B [A-F] CUT RESISTANCE ISO 13997
P [P] IMPACT RESISTANCE (OPTIONAL)

EN 407
X [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Impact-resistant glove
Mechanical Glove Type	Tricot
Fiber	SOFTnocut
Coating Level	Hand Coated
Number of Coatings	Single Coated
Gauge	13
Benefits element	Reach, Vendor pack
Color	Black
Size	9
Type of conditioning	Header card

Packaging

Sale unit: Header card
60 pairs /box

Safety gloves

EOS FLEX CUT B VV921

SLIGHTLY SHARP AND NON INTENSIVE WORK

Anti-impact glove with level B cut resistance, flexible and comfortable, ideal for heavy-duty work in dry conditions.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
GOI921KH01BK09 [VV921NO09]	Black	09	EOS FLEX CUT B VV921	3295249268619	13295249268616	60	6	18.14 kg	73.5 cm	28.5 cm	36.5 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height