# EOS FLEX CUT B VV921

## 轻度切割的零散作业

手部防护

抗冲击手套具有 B 级防割性能，柔软舒适，是在干燥条件下从事重体力劳动的理想选择。



## 具体优势

### 高性能

· 高性能HEATnocut纤维使其具备高温耐接触性 (100°C可持续15秒)
· 灵活性加强，提升对冲击和挤压的防护
· SOFTnocut纤维提供优秀的防割性能

## 应用行业

- 农业
- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 汽车业

## 标准和认证

CE 2类

**EN 388**
3 X 4 2 B P

**EN 407**
X 2 X X X X

**ANSI ISEA 138**
性能等级：1

## 防范风险

高温　冲击　切割　磨损

手部防护

# EOS FLEX CUT B VV921

## 轻度切割的零散作业

抗冲击手套具有 B 级防割性能，柔软舒适，是在干燥条件下从事重体力劳动的理想选择。

## 详细信息 - 标准

**EN388:2016+A1:2018**
3 [0-4] 耐磨
X [0-5] 防切割
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
B [A-F] CUT RESISTANCE ISO 13997
P [P] IMPACT RESISTANCE (OPTIONAL)

**EN 407**
X [0-4] 燃烧性能
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

## 技术细节

| | |
|---|---|
| 手套类别 | 特殊手套 |
| 手套类别 | 抗冲击手套 |
| 机械手套类 | 针织 |
| 纬纱 | SOFTnocut（高密度聚乙烯/氨纶/聚酰胺混合料） |
| 涂层水平 | 除手腕外全涂层 |
| 涂层数 | 单涂层 |
| 针数 | 13 |
| 产品优势 | Reach, 供应商包装 |
| 颜色 | 黑色 |
| 尺码 | 9 |
| 包装类型 | 标题卡 |

## 包装

销售单位: 标题卡
60 成对/箱

Safety gloves

# EOS FLEX CUT B VV921

## SLIGHTLY SHARP AND NON INTENSIVE WORK

Anti-impact glove with level B cut resistance, flexible and comfortable, ideal for heavy-duty work in dry conditions.

## Logistics information

| Reference | Colour | Size | Designation | EAN13 | Box code | | | Weight | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| GOI921KH01BK09 [ VV921NO09 ] | Black | 09 | EOS FLEX CUT B VV921 | 3295249268619 | 13295249268616 | 60 | 6 | 18.14 kg | 73.5 cm | 28.5 cm | 36.5 cm |

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height