

VENICUTD01

LONG-LASTING CUT WORK

Level D cut-resistant glove with good thermal resistance, ideal for use in oily or aqueous environments



Specific benefits



Hygiene

· Nitrile means no risk of allergies for users



Performance

- \cdot The high-performance HEAT nocut fiber provides excellent abrasion and cut resistance
- ·The nitrile coating gives people working in oily/greasy environments an excellent grip on the objects they handle
- The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Certifications and norms





EN 388

4 X 4 2 D



EN 407×1××××



Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Mining

Risk Protection











VENICUTD01

LONG-LASTING CUT WORK

Level D cut-resistant glove with good thermal resistance, ideal for use in oily or aqueous environments

Standards - Details



EN388:2016+A1:2018

4 [0-4] ABRASION RESISTANCE X [0-5] CUT RESISTANCE 4 [0-4] TEAR RESISTANCE 2 [0-4] PIERCE RESISTANCE D [A-F] CUT RESISTANCE ISO 13997

Technical details

Mechanical glove
nitted coated glove
ricot
litrile foam
alm Coating
ingle Coated
3
ellow-Grey-Black
, 8, 9, 10
n individual bags







VENICUTD01

LONG-LASTING CUT WORK

Level D cut-resistant glove with good thermal resistance, ideal for use in oily or aqueous environments

Logistics Information Reference Color Size Designation EAN13 Box Code Weight 31.8 77.4 VECUTD01GJ07 Yellow-Grey-Black 07 VENICUTD01 3295249235673 13295249235670 12 60 6.6 kg 20.6 31.6 78.2 VECUTD01GJ08 Yellow-Grey-Black 08 VENICUTD01 3295249235680 13295249235687 60 12 6.7 kg cm cm cm 19.6 31.4 77.8 VECUTD01GJ09 Yellow-Grey-Black 09 VENICUTD01 3295249235697 13295249235694 7.6 kg 60 12 cm cm cm 19.0 31.2 78.0 VENICUTD01 VECUTD01GJ10 Yellow-Grey-Black 10 3295249235703 13295249235700 7.7 kg 12 cm cm 22.2 31.2 75.6 VECUTD01GJ11 Yellow-Grey-Black 11 VENICUTD01 3295249235710 13295249235717 60 8.3 kg 12

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height





cm

cm