

VENICUTB00

SLIGHTLY SHARP AND NON INTENSIVE WORK

Uncoated, level D cut-resistant glove, ideal for the food industry



Certifications and norms





EN 388 3 X 4 X B





ANSI ISEA 105

Specific benefits



Durability

· Tested before and after washing: performance unchanged



Easy to use

· Perfect fit so that users do not feel any discomfort in the wrist area with prolonged use



Hygiene

· Washable glove, so it can be reused



Performance

· Lightweight for optimal dexterity



Compatibility

· Compatible with food

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Manufacturing/Transformation
- Accomodation & Food services
- Maintenance







VENICUTB00

SLIGHTLY SHARP AND NON INTENSIVE WORK

Uncoated, level D cut-resistant glove, ideal for the food industry

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE X [0-5] CUT RESISTANCE 4 [0-4] TEAR RESISTANCE X [0-4] PIERCE RESISTANCE B [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Knitted uncoated glove
Mechanical glove kind	Knitted
Gauge	15
Cuff caracteristic	Long cuff
Cuff length	100 mm
Benefits element	Reach, Washable, Vendor pack, Long cuff (>290mm)
Color	Blue-White
Size	6, 7, 8, 9, 10, 11
Type of packaging	in individual bags







VENICUTB00

SLIGHTLY SHARP AND NON INTENSIVE WORK

Uncoated, level D cut-resistant glove, ideal for the food industry

Logistics information										
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight		
VECUTB00BL06	Blue-White	06	VENICUTB00	3295249255206	13295249255203	60	12	3.5 kg		
VECUTB00BL07	Blue-White	07	VENICUTB00	3295249255442	13295249255449	60	12	3.6 kg		
VECUTB00BL08	Blue-White	08	VENICUTB00	3295249255459	13295249255456	60	12	3.9 kg		
VECUTB00BL09	Blue-White	09	VENICUTB00	3295249255466	13295249255463	60	12	4.0 kg		
VECUTB00BL10	Blue-White	10	VENICUTB00	3295249255473	13295249255470	60	12	4.3 kg		
VECUTB00BL11	Blue-White	11	VENICUTB00	3295249255480	13295249255487	60	12	4.0 kg		



