



Hand protection

FB149

WORKS IN DRY ENVIRONMENT

Highly durable, comfortable to wear, mechanical leather glove, ideal for dry conditions



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance

Certifications and norms



EN 388
3 1 2 2 X



Hand protection

FB149

WORKS IN DRY ENVIRONMENT

Highly durable, comfortable to wear, mechanical leather glove, ideal for dry conditions

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Thickness	1,1 -> 1,3 mm
Cuff characteristic	Sewn open cuff with elastic
Color	Beige
Size	8, 9, 10
Type of packaging	Pack of 12



Gants de protection

FB149

TRAVAUX MILIEU SEC

Gant mécanique cuir, agréable au porter, avec une grande durabilité, idéal en milieu sec

Informations logistiques

Référence	Couleur	Taille	Désignation	EAN 13	Code carton	PCB	SPCB	Poids
FB14908	Beige	08	FB149	3295249000387	13295249000384	120	12	12.9 kg
FB14909	Beige	09	FB149	3295249000394	13295249000391	120	12	16.3 kg
FB14910	Beige	10	FB149	3295249000400	13295249000407	120	12	14.8 kg