



Hand protection

FB149

WORKS IN DRY ENVIRONMENT

Highly durable, comfortable to wear, mechanical leather glove, ideal for dry conditions



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance

Certifications and norms



EN 388
3 1 2 2 X

Protects against risks



Wearing



Hand protection

FB149

WORKS IN DRY ENVIRONMENT

Highly durable, comfortable to wear, mechanical leather glove, ideal for dry conditions

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE

1 [0-5] CUT RESISTANCE

2 [0-4] TEAR RESISTANCE

2 [0-4] PIERCE RESISTANCE

X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Thickness (mm)	1,1 -> 1,3
Cuff characteristic	Sewn open cuff with elastic
Color	Beige
Size	8, 9, 10
Type of packaging	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
120 pairs /box



Safety gloves

FB149

WORKS IN DRY ENVIRONMENT

Highly durable, comfortable to wear, mechanical leather glove, ideal for dry conditions

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
GLFB14UD01BE08 [FB14908]	Beige	08	FB149	3295249000387	13295249000384	120	12	12.9 kg	30.6 cm	61.4 cm	30.0 cm
GLFB14UD01BE09 [FB14909]	Beige	09	FB149	3295249000394	13295249000391	120	12	16.3 kg	28.6 cm	62.2 cm	29.2 cm
GLFB14UD01BE10 [FB14910]	Beige	10	FB149	3295249000400	13295249000407	120	12	14.8 kg	28.6 cm	62.0 cm	27.8 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height