



# CADEROUSSE S3 SRC

COLD ENVIRONMENT

Fur-lined ranger with a wider fit and robust construction, for the construction industry

Foot protection



## Specific benefits



### Comfort

- Stabilisation of the foot when walking
- Shock-absorbing heel to relieve joint strain
- Wide shape to accommodate stronger foot morphologies
- Dual-density outsole



### Performance

- High stability ensured by the sole's grip properties

## Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Light Industry
- Maintenance
- Automotive

## Certifications and norms



EN ISO 20345

S3 CI WPA FO A E SR

## Risk Protection



Antistatic



Shock



Cold



Slip



*enjoy safety.*

Edit 08/03/2025  
www.deltaplus-usa.com



# CADEROUSSE S3 SRC

COLD ENVIRONMENT

Fur-lined ranger with a wider fit and robust construction, for the construction industry

Foot protection

## Standards - Details

## Technical details

Type of Shoe	High Cut Shoe
Outsole material	PU, 2d
Anti-perforation insert	Stainless steel
Upper material	Leather
Upper finition material	Grain Leather, Water repellent
Safety toe-cap	Stainless steel
Lining material	Textile, Polyester, Synthetical-fur
Footbed material	Felt
Footbed characteristic	Removable, Breathable, Pre-molded
Outsole finition	Injected
Weight (g per shoe)	852
Size range	39 → 48








Foot protection

# CADEROUSSE S3 SRC

## COLD ENVIRONMENT

Fur-lined ranger with a wider fit and robust construction, for the construction industry

### Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
CADERS3NO41	Black	8	CADEROUSSE S3 SRC	3295249114084	13295249114081	5	1	11.0 kg	32.5 cm	68.2 cm	36.5 cm
CADERS3NO43	Black	10	CADEROUSSE S3 SRC	3295249114107	13295249114104	5	1	11.3 kg	35.6 cm	65.6 cm	31.8 cm
CADERS3NO44	Black	11	CADEROUSSE S3 SRC	3295249114114	13295249114111	5	1	11.6 kg	35.8 cm	65.4 cm	31.6 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height