



Fall protection

AN218S200CDD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges



Durability

- Thermo-retractable tube to extend the life of lanyards

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive
- Power Energy



Fall protection

AN218S200CDD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.

Standards - Details

Technical details

Type of equipment	Braided rope with thimbled loops
Composition of the main support	Steel, Polyamide, Polyester
Length	2 m
Rope diameter	10,5 mm
With connector	yes
Color	White-Black
Connector (user side)	Screw carabiner, steel, opening 18mm
SIZE	2 m
Benefits element	Leading edge
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Weight	1,97 kg
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Absturzsicherung

AN218S200CDD

ENERGY ABSORBING LANYARDS

Kompaktes, 2 Meter langes Lanyard mit doppelter Energieabsorption mit patentiertem System, das Bewegungsfreiheit für kurze Wege gewährleistet

Logistische Informationen

Referenz	Farbe	Größe	Bezeichnung	EAN 13	Karton-Code	PCB	SPCB	Gewicht
AN218S200CDD	Weiß-Schwarz	2 m	AN218S200CDD	3295249235901	13295249235908	5	1	10.8 kg