



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Standards - Details

Technical details

Type of equipment	Energy absorber in lanyard webbing
Composition of the main support	Steel, Polyester
Length	2 m
With connector	yes
Color	Orange
Connector (user side)	Screw carabiner, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing	10 years
Weight	1,6 kg
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



защита от падения

AN213200ZDD

ENERGY ABSORBING LANYARDS

Двойная энергопоглощающая стропа, с высокопрочным ремнем, с 2-мя широко раскрывающимися крюками, для перемещений на короткие расстояния

Логистическая информация

Ссылка	Цвет	Размер	Назначение	EAN 13	Код коробки	PCB	SPCB	Вес
AN213200ZDD	Оранжевый	2 м	AN213200ZDD	3295249265083	13295249265080	5	1	9.47 kg