



Fall protection

# HAR42EL

## FALL ARRESTER HARNESSES

Insulating harness for electrical risks



### Specific benefits



#### Hygiene

- Harnesses and textiles can be washed with neutral soap



#### Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg



#### Easy to use

- NFC system guarantees traceability

### Certifications and norms



EN361

140 KG

### Applications

- Building
- Chemical industry
- Oil & Gas (extraction)
- Petrochemical
- Power Energy
- Storage



Fall protection

# HAR42EL

## FALL ARRESTER HARNESSES

Insulating harness for electrical risks

### Standards - Details

### Technical details

Type of equipment	Fall arrester harness - dielectric
Composition of the main support	Steel, Plastic, Polyester
Fastening	Buckles
Total number of attachment points for the fall arrester	2
Anti-fall point	Dorsal, Sternal
Color	Black-Grey
SIZE	S/M/L
Lifespan from manufacturing	10 years
Weight	0,922 kg
Number of manual buckles	2
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Long vertical movement or movement on inclined surface, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Proteção anti-quedas

# HAR42EL

## ARNÊS ANTI-QUEDAS

Arnês isolante para riscos elétricos

### Informação logística

Referência	Cor	Tamanho	Designação	EAN 13	Código da caixa	PCB	SPCB	Peso
HAR42ELGT	Preto-Cinzent	S/M/L	HAR42EL	3295249203481	13295249203488	5	1	6.24 kg
HAR42ELXX	Preto-Cinzent	XL/XXL	HAR42EL	3295249203498	13295249203495	5	1	6.3 kg