



Fall protection

PROTECTOR TETRA AN15006F

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres



Specific benefits



Performance

- Certification above the maximum rated load of 100 kg: product certified at 150 kg



Easy to use

- Automatic carabiners for secure and time-saving locking
- Carrying handle for easy transport
- NFC system guarantees traceability



Durability

- Impact-resistant ABS housing



Visibility

- Visual fall indicator for instant verification that the product is working properly

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage

Certifications and norms



EN360

RFU 11.062
150 KG



Fall protection

PROTECTOR TETRA AN15006F

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Galvanized steel
ARA lenght	6 m
ARA lenght	236.2206 inch
Cable diameter	4 mm
Included elements	Included energy absorber
Color	Orange
Connector (user side)	Self-locking hook, steel, opening 11 mm
SIZE	6 m
Benefits element	Fall indicator
Lifespan from manufacturing	20 years
Weight	5,6 kg
Maximum load for one person	150 kg
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface
Locking system	Inertia locking system



защита от падения

PROTECTOR TETRA AN15006F

RETRACTABLE FALL ARRESTERS

Барабан с автоматическим втягиванием для перемещения на расстояние до 6 метров

Logistics Information

Ссылка	Цвет	Размер	Назначение	EAN 13	Код коробки	PCB	SPCB	Вес
AN15006F	Оранжевый	6 м	PROTECTOR TETRA AN15006F	3295249195496	13295249195493	1	1	5.6 kg