

PROTECTOR TETRA AN14006F

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres



Certifications and norms



EN360

RFU 10.060 HORIZONTAL CERTIFICATION

Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Easy to use

- · Carrying handle for easy transport
- · NFC system guarantees traceability



Durability

· Impact-resistant ABS housing



Visibility

 \cdot Visual fall indicator for instant verification that the product is working properly

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage







PROTECTOR TETRA AN14006F

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Webbing reel				
Composition of the main support	ABS (Acrylonitrile Butadiene Styrene), Polyester				
Strap width	25 mm				
ARA lenght	6 m				
ARA lenght	236.2206 inch				
Included elements	Included energy absorber				
Color	Orange				
Connector (user side)	Automatic lock hook, steel, opening 22mm				
SIZE	6 m				
Benefits element	Fall indicator				
Lifespan from manufacturing	10 years				
Weight	5,4 kg				
Maximum load for one person	100 kg				
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure				
Locking system	Inertia locking system				







PROTECTOR TETRA AN14006F

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Logistics information										
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight		
AN14006F	Orange	6 m	PROTECTOR TETRA AN14006F	3295249195458	13295249195455	1	1	5.4 kg		



