



# LO030100

## LANYARDS

1 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection



## Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

## Certifications and norms



EN354

EN 795  
TYPE B

## Protects against risks



Fall



# LO030100

## LANYARDS

1 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

### Standards - Details

### Technical details

Type of equipment	Webbing lanyard and anchorage point
Composition of the main support	Polyester
Strap width (mm)	25
Length (m)	1
Width (inch)	0.9825
Width (mm)	25
Color	Black-Orange
Ending	2 sewn loops
Weight (kg)	0,070
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	3.2808



# LO030100

## LANYARDS

Fall protection

1 metre webbing lanyard and anchorage point, allowing maximum versatility

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANC03PO001011 [ LO030100 ]	Black-Orange	1 m	LO030100	3295249215859	13295249215856	15	1	2.5 kg	14.5 cm	38.0 cm	16.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height