



Oprema protiv pada

LV105

NAPRAVE ZA UČVRŠĆENJE

Sidrena šipka od nehrđajućeg čelika radi sprječavanja korozije



Područje upotrebe

- Poljoprivreda
- Zgrada
- Pomoćni poslovi / Obrtništvo
- Održavanje
- Kemijska industrija
- Nafta i plin (vađenje)

Certifikati i standardi



EN 795
TIP A

Štiti od



Pad



LV105

NAPRAVE ZA UČVRŠĆENJE

Sidrena šipka od nehrđajućeg čelika radi sprječavanja korozije

Oprema protiv pada

Pojedinosti - Standardi

Tehnički detalji

Vrsta opreme	Šipka za učvršćenje s ušicom od nehrđajućeg čelika
Sastav glavnog nosača	Nehrđajući čelik
Duljina (m)	0,14
Boja	Boja čelika
Težina (kg) (kg)	0,174
Otpornost (Kn)	12kN
Maksimalni broj korisnika	1
Radne situacije za zaštitu od pada	Zadržavanje, Spašavanje i evakuacija, Dugotrajno vertikalno kretanje ili kretanje na kosoj podlozi, Dugotrajno vertikalno kretanje ili kretanje na kosoj podlozi za radove na užetu, Kratkotrajno vertikalno kretanje ili kretanje na kosoj podlozi (- 3m), Dugotrajno horizontalno kretanje na horizontalnoj podlozi, Dugotrajno horizontalno kretanje na vertikalnoj podlozi, Kratkotrajno horizontalno kretanje (- 3m)
Duljina (ft)	0.4594
Diameter (mm)	12



Fall protection

LV105

ANCHORAGE DEVICES

Stainless steel anchorage rod for sealing to prevent corrosion

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANC07SS0Z1011 [LV105]	Steel	One size	LV105	3660348006170	13660348006177	10	1	2.6 kg	34.5 cm	11.5 cm	14.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height