Protipádová ochrana

TRA22

OCHRANA PŘI PRÁCI VE VÝŠKÁCH A ZÁCHRANA Z ÚZKÝCH PROSTOR

Hliníkový stativ do 2 metrů, se 2 nosnými deskami, lehký, se snadnou instalací, pro všechny druhy práce ve stísněných prostorách



Použití

- **Budova**
- **Dokončovací stavební práce / řemesla**
- **Údržba**
- **Chemický průmysl**
- **Ropa & plyn (těžba)**
- **Těžební průmysl**

Certifikace a normy

CE KATEGORIE III

EN 795
TYP B

TS16415
3

Chrání před riziky

Pád

Protipádová ochrana

TRA22

OCHRANA PŘI PRÁCI VE VÝŠKÁCH A ZÁCHRANA Z ÚZKÝCH PROSTOR

Hliníkový stativ do 2 metrů, se 2 nosnými deskami, lehký, se snadnou instalací, pro všechny druhy práce ve stísněných prostorách

Podrobnosti - Normy

Technické detaily

Typ zařízení	Teleskopický stativ
Materiálové složení	Hliník
Kotevní zařízení	Stativ
Max. délka (m)	1,97
Min. délka (m)	1,25
Barva	Hliníková
Váha (kg) (kg)	17,4
Odpor (Kn)	20
Rozvor (m)	1,89
Není v ceně	Schůdky TRA103
Možnosti zabezpečení práce ve výškách	Záchrana a evakuace, Vertikální pohyb v uzravřeném prostoru



Fall protection

TRA22

FALL ARREST AND RESCUE, CONFINED SPACE

Aluminium tripod up to 2 metres, with 2 support plates, light and easy to install for all types of work in confined spaces

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANCF2AL1Z9021 [TRA22]	Aluminium-coloured	Adjustable	TRA22	3295249194093	13295249194090	1	1	23.75 kg	150.5 cm	30.5 cm	28.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height