



Valbescherming

TRA22

VALBEVEILIGING EN RESCUE, BESLOTEN RUIMTES

Aluminium statief tot 2 meter, met 2 steunplaten, licht en eenvoudig te installeren voor alle soorten werk in krappe ruimtes



Toepassing

- **Bouw & Constructie**
- **Afwerking / ambachtslieden**
- **Onderhoud**
- **Chemische industrie**
- **Olie en Gas(winning)**
- **Mijnbouw**

Certificeringen en normen

CE CATEGORIE III

EN 795
TYPE B

TS16415
3

Beschermt tegen



Val



Valbescherming

TRA22

VALBEVEILIGING EN RESCUE, BESLOTEN RUIMTES

Aluminium statief tot 2 meter, met 2 steunplaten, licht en eenvoudig te installeren voor alle soorten werk in krappe ruimtes

Normen - Details

Technische details

Soort uitrusting	Telescopisch statief
Verankeringsselement	Statief
Samenstelling van de hoofdsteun	Aluminium
Lengte max. (m)	1,97
Lengte min. (m)	1,25
Kleur	Aluminium
Gewicht (kg) (kg)	17,4
Weerstand (Kn)	20
Grond basis (m)	1,89
Niet inbegrepen	Trede TRA103
Werksituaties met valbeveiliging	Redding en evacuatie, Vertikale verplaatsingen in een beperkte ruimte



Fall protection

TRA22

FALL ARREST AND RESCUE, CONFINED SPACE

Aluminium tripod up to 2 metres, with 2 support plates, light and easy to install for all types of work in confined spaces

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANCF2AL1Z9021 [TRA22]	Aluminium- coloured	Adjustable	TRA22	3295249194093	13295249194090	1	1	23.75 kg	150.5 cm	30.5 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height