



L0030200

LANYARDS

2 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)
- Mining



Certifications and norms



EN354

EN 795
TYPE B

Risk Protection



Fall



LO030200

LANYARDS

2 metre webbing lanyard and anchorage point, allowing maximum versatility

Fall protection

Standards - Details

Technical details

Type of equipment	Webbing lanyard and anchorage point
Composition of the main support	Polyester
Length (m)	2
Width (inch)	0.9825
Width (mm)	25
Color	Black-Orange
Ending	2 sewn loops
Weight (kg)	0,218
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Length (ft)	6.5616








LO030200

LANYARDS

Fall protection

2 metre webbing lanyard and anchorage point, allowing maximum versatility

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
LO030200	Black-Orange	2 m	LO030200	3295249215873	13295249215870	15	1	3.6 kg	22.0 cm	31.0 cm	16.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height