

HAR12

FALL ARRESTER HARNESSES

Harness with 2 anchorage points and two-coloured straps for intuitive fitting, for occasional wearers



Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

 \cdot Certification above the maximum rated load of 100 kg: product certified at 140 kg



Easy to use

- · Two-tone strap for easy harness fitting
- · NFC system guarantees traceability

Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Forestry
- Storage

Certifications and norms



EN361 140 KG







HAR12

FALL ARRESTER HARNESSES

Harness with 2 anchorage points and two-coloured straps for intuitive fitting, for occasional wearers

Standards - Details

Technical details

Type of equipment	Fall arrester harness			
Composition of the main support	Steel, Polyester			
Adjustment	2 adjustable lateral plates			
Fastening	Buckles			
Total number of attachment points for the fall arrester	2			
Buckles	Manual loop			
Anti-fall point	Dorsal, Sternal			
Color	Orange			
SIZE	S/M/L			
Lifespan from manufacturing	10 years			
Weight	0,730 kg			
Number of manual buckles	2			
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Long vertical movement or movement on inclined surface, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space, Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection			







HAR12

FALL ARRESTER HARNESSES

Harness with 2 anchorage points and two-coloured straps for intuitive fitting, for occasional wearers

Logistics Information										
Reference	Color	Size	Designation	EAN13	Box Code	Multiple Sales	Minimum Order Quantity	Weight		
HAR12GT	Orange	SM/MD/LG	HAR12	3295249180553	13295249180550	10	1	8.5 kg		
HAR12XX	Orange	XL/2X	HAR12	3295249180348	13295249180345	10	1	8.7 kg		



