



Fall protection

AN245200ADD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Specific benefits



Comfort

- Elastic webbing lanyard for easy movement and safety



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 140kg
- Webbing with better abrasion resistance and certified against sharp edges



Ease of Use

- Automatic carabiners for secure locking and time saving
- NFC system guarantees traceability

Applications

- Public Works
- Finishing Works/Craftsmanship
- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Mining

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG



Fall protection

AN245200ADD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Elastic strap with thimbled loops
Composition of the main support	Steel, Polyester
With connector	yes
Color	Black-Orange
Connector 1	Automatic lock hook, steel, opening 16mm
SIZE	1.40 to 2 m
Ending	2 thimble ferrule loops
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing	10 years
Weight	1,67 kg
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Fall protection

AN245200ADD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN245200ADD	Black-Orange	1.40 2 m	AN245200ADD	3295249265137	13295249265134	5	1	9.9 kg