



坠落防护

AN218R2ADD

能量吸收带

双大钩减震绳，长度可调节，必要时减少气流影响



具体优势



卫生环保

· 系带和织物面料可用中性肥皂洗涤



高性能

· 认证的最大额定负载在100kg以上：产品认证在140kg以下
· 系带的耐磨性增强，通过可在锐物边缘使用的认证

应用行业

- 公共工程
- 终饰工程/工艺
- 汽车业
- 仓储

标准和认证



EN355

水平认证 - 140 KG
RFU 11.062
140 KG

防范风险



坠落



enjoy safety.

编辑 25/07/2026
www.deltaplus.com.cn



坠落防护

AN218R2ADD

能量吸收带

双大钩减震绳，长度可调节，必要时减少气流影响

详细信息 - 标准

技术细节

装备类型	编织绳
主要支架的组成	钢, 玻璃纤维, 支撑材料/聚酯纤维
长度 (m)	2
调节	可通过绳索上的减速环进行调节
绳索直径 (mm)	12
带有连接器	是
颜色	白色-黑色
连接器 (用户方)	小钩，钢制，开口19mm
终端件	1个缝制套环
连接器 (结构方)	2个自动锁钩，钢质，开口 55 毫米
自生产之日起的产品寿命 (年)	10
重量 (kg)	1,97
防坠落作业类型	生命线上的移动, 短距离垂直移动或倾斜表面上的移动（小于3米），短距离水平移动 (小于3米), 具有多重连接/断开功能的长距离移动
长度 (ft)	6.5616



Fall protection

AN218R2ADD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard with adjustable length allowing the length to be adjusted and therefore reducing the air draft, if necessary

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAD3002DZ021 [AN218R2ADD]	White-Black	1.50 → 2 m	AN218R2ADD	3295249265106	13295249265103	5	1	11.54 kg	29.5 cm	45.5 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height