Protezione anticaduta

LO147150CDD

FUNI

Doppio cordino da 1,5 metri con connettore ad ampia apertura per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.

Campi di utilizzo

- **Edificio**
- **Finitura / artigiani**
- **Manutenzione**
- **Industria chimica**
- **Petrolio e gas minerario (estrazione)**
- **Industria mineraria**

Certificazioni e norme

CE CATEGORIA III

EN354

Protegge contro i rischi

Caduta

Protezione anticaduta

LO147150CDD

FUNI

Doppio cordino da 1,5 metri con connettore ad ampia apertura per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.

Dettagli - Norme

Dettagli tecnici

Tipo di attrezzatura	Corda intrecciata
Composizione del supporto principale	Acciaio, Poliammide
Lunghezza (m)	1,5
Diametro della fune (mm)	10,5
Con connettore	si
Colore	Bianco
Connettore (lato utilizzatore)	Moschettone a vite, acciaio, apertura 18 mm
Terminazione	1 occhiello cucito
Connettore (lato struttura)	2 connettori a chiusura automatica, acciaio, apertura 55 mm
Peso (kg) (kg)	1,4
Situazioni di lavoro	Trattenuta
Lunghezza (ft)	4.9213

LO147150CDD

LANYARDS

Fall protection

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
LIN01Z51031Z5 [LO147150CDD]	White	1.50 m	LO147150CDD	3660348006361	13660348006368	5	1	7.5 kg	20.6 cm	53.5 cm	14.5 cm

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height