



Fall protection

L0007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Oil & Gas (extraction)
- Mining
- Power Energy



Certifications and norms



EN354

Protects against risks



Fall



Fall protection

L0007150CD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

Type of equipment	Twisted rope
Composition of the main support	Steel, Polyamide
Length (m)	1,5
Rope diameter (mm)	12
With connector	yes
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
Ending	End spliced with thimble loop
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Weight (kg)	0,850
Fall arrest work situations	Restraint
Lenght (ft)	4.9213



LO007150CD

LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LIN01Z51041Z5 [LO007150CD]	White	1.50 m	LO007150CD	3660348006347	13660348006344	15	1	14.3 kg	29.0 cm	44.2 cm	24.4 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height