Protezione anticaduta

LO007150CD

FUNI

Cordino da 1,5 metri con connettore a grande apertura, per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.

Campi di utilizzo

- **Edificio**
- **Finitura / artigiani**
- **Manutenzione**
- **Petrolio e gas minerario (estrazione)**
- **Industria mineraria**
- **Energie**

Certificazioni e norme

CE CATEGORIA III

EN354

Protegge contro i rischi

Caduta

Protezione anticaduta

LO007150CD

FUNI

Cordino da 1,5 metri con connettore a grande apertura, per una massima versatilità e per il collegamento a qualsiasi tipo di struttura.

Dettagli - Norme

Dettagli tecnici

Tipo di attrezzatura	Corda trefolata
Composizione del supporto principale	Acciaio, Poliammide
Lunghezza (m)	1,5
Diametro della fune (mm)	12
Con connettore	si
Colore	Bianco
Connettore (lato utilizzatore)	Moschettone a vite, acciaio, apertura 18 mm
Terminazione	Estremità impiombata con occhiello a ditale
Connettore (lato struttura)	1 Connettore a chiusura automatica, acciaio, apertura 55 mm
Peso (kg) (kg)	0,850
Situazioni di lavoro	Trattenuta
Lunghezza (ft)	4.9213

LO007150CD

LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
LIN01Z51041Z5 [LO007150CD]	White	1.50 m	LO007150CD	3660348006347	13660348006344	15	1	14.3 kg	29.0 cm	44.2 cm	24.4 cm

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height