



Fall protection

# L0007150CD

## LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



## Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Oil & Gas (Extraction)
- Mining
- Power Energy

## Certifications and norms



EN354

## Risk Protection



Fall



# L0007150CD

## LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Standards - Details

### Technical details

Type of equipment	Twisted rope
Composition of the main support	Steel, Polyamide
Length (m)	1,5
Rope diameter (mm)	12
With connector	yes
Color	White
Connector 1	Screw carabiner, steel, opening 18mm
Ending	End spliced with thimble loop
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Weight (kg)	0,850
Fall arrest work situations	Restraint
Lenght (ft)	4.9213








# LO007150CD

## LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LIN01Z51041Z5 [LO007150CD]	White	1.50 m	LO007150CD	3660348006347	13660348006344	15	1	14.3 kg	29.0 cm	44.2 cm	24.4 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height