



Fall protection

AN208S200CD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges



Durability

- Thermo-retractable tube to extend the life of lanyards

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive
- Power Energy

Protects against risks



Fall



Fall protection

AN208S200CD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances

Standards - Details

Technical details

Type of equipment	Energy-absorbing lanyard made of braided rope with thermoformable sheath
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Rope diameter (mm)	10,5
With connector	yes
Color	White-Black
Connector (user side)	Screw carabiner, steel, opening 18mm
Benefits element	Leading edge
Ending	1 loop sewn thimble
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Weight (kg)	1,27
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616



Fall protection

AN208S200CD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS6002DC011 [AN208S200CD]	White-Black	2 m	AN208S200CD	3295249235895	13295249235892	5	1	6.9 kg	30.0 cm	44.6 cm	18.6 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height