



Valbescherming

EX030200

WERKPOSITIONERINGSSYSTEMEN

Positioneringskoord van 2 meter, voor een vlotte en optimale aanpassing, uitgerust met een optioneel vergrendelingssysteem



Toepassing

- Landbouw
- Bouw & Constructie
- Afwerking / ambachtslieden
- Onderhoud
- Chemische industrie
- Mijnbouw

Certificeringen en normen



EN358

Beschermt tegen



Val



Valbescherming

EX030200

WERKPOSITIONERINGSSYSTEMEN

Positioneringskoord van 2 meter, voor een vlotte en optimale aanpassing, uitgerust met een optioneel vergrendelingssysteem

Normen - Details

Technische details

Soort uitrusting	Werkpositioneringssysteem
Samenstelling van de hoofdsteun	Polyamide
Lengte max. (m)	2
Lengte min. (m)	0,20
Lengte (m)	2
Diameter touw (mm)	10,5
Met connector	ja
Kleur	Wit
Connector (gebruikerszijde)	Karabijnhaak met schroefsluiting, staal, opening 18 mm
Connector (structuurzijde)	Kleine haak, staal, opening 21 mm
Werksituaties met valbeveiliging	Positionering, Positionering
Lengte (ft)	6.5616



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS0002AC011 [EX030200]	White	0.20 → 2 m	EX030200	3660348005166	13660348005163	5	1	6.35 kg	27.0 cm	47.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height