



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system



Applications

- Agriculture
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Mining

Certifications and norms



EN358

Risk Protection



Fall



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system

Standards - Details

Technical details

Type of equipment	Work positioning system
Composition of the main support	Polyamide
Max. length (m)	2
Min. length (m)	0,20
Length (m)	2
Rope diameter (mm)	10,5
With connector	yes
Color	White
Connector 1	Screw carabiner, steel, opening 18mm
Connectors (structure side)	Small hook, steel, opening 21 mm
Fall arrest work situations	Work positioning, Restraint
Lenght (ft)	6.5616



Fall protection

EX030200

WORK POSITIONING SYSTEMS

2 metre positioning lanyard, allowing for smooth and optimal adjustment, with optional locking system

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS0002AC011 [EX030200]	White	0.20 → 2 m	EX030200	3660348005166	13660348005163	5	1	6.35 kg	27.0 cm	47.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height