Fall protection

AN245200CDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Applications

- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Chemical Industry**
- **Oil & Gas (Extraction)**
- **Mining**

Certifications and norms

CE CATEGORY III

EN355

Risk Protection

Fall

DELTAPLUS

enjoy safety.

Edit 03/11/2026

www.deltaplus-usa.com

Fall protection

AN245200CDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
Color	Black-Orange
Connector 1	Screw carabiner, steel, opening 18mm
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



Proteção contra quedas

AN245200CDD

SISTEMAS DE POSICIONAMENTO E RESTRIÇÃO DE TRABALHO

Cordão duplo de absorção de energia feito de tecido elástico leve, proporcionando liberdade de movimento

Informação logística

Referência	Cor	Tamanho	Designação	EAN 13	Código da caixa			Peso			
ENAD4002DC021 [AN245200CDD]	Preto-Laranja	Entre 1,40 e 2 m	AN245200CDD	3295249194222	13295249194229	5	1	9.198 kg	29.4 cm	43.4 cm	15.2 cm

Caixa completa

Mínimo venda

Largura da caixa

Profundidade da caixa

Altura da caixa