Düşme önleme

AN245200CDD

ENERJİ SÖNÜMLEYİCİ HALATLAR

Hareket özgürlüğü sağlayan hafif elastik dokumadan yapılmış çift enerji emici kordon



Uygulamalar

- **Yapı**
- **İkinci iş / Zanaatkarlar**
- **Bakım**
- **Kimya endüstrisi**
- **Petrol ve Gaz (çıkarma)**
- **Maden endüstrisi**

Sertifikalar ve standartlar

CE KATEGORİ III

EN355

Karşı korur

Düşme



Düşme önleme

AN245200CDD

ENERJİ SÖNÜMLEYİCİ HALATLAR

Hareket özgürlüğü sağlayan hafif elastik dokumadan yapılmış çift enerji emici kordon

Detaylar - Standartlar

Ürün bilgileri

Ekipman Türü	Streç dokuma kordon
Ana destek yapısı	Çelik, Polyester
Uzunluk (m)	2
Renk	Siyah-Turuncu
Konektör (kullanıcı tarafı)	Vidalı karabina, çelik, açıklık 18 mm
Konnektör (yapı tarafı)	2 otomatik kilit kancası, çelik, 55 mm açıklık
Üretimden itibaren raf ömrü (yıllar)	10
Düşmeye karşı çalışma koşulları	Sabit yapılarda dikey hareket, Kurtarma halatı üzerinde hareket, Kısa dikey hareket ya da eğimli yüzeylerde hareket (3m'den az), Kısa yatay hareket (3m'den az), Çoğlu bağlantı/bağlantısız uzun hareket
Uzunluk (ft)	6.5616

AN245200CDD

ENERGY ABSORBING LANYARDS

Fall protection

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAD4002DC021 [AN245200CDD]	Black-Orange	1.40 → 2 m	AN245200CDD	3295249194222	13295249194229	5	1	9.198 kg	29.4 cm	43.4 cm	15.2 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height