



Hand protection

EOS FLEX CUT D VV922

LONG-LASTING CUT WORK

Impact-resistant glove with level D cut protection for the whole hand, ideal for multi-purpose work in aqueous or oily environments



Specific benefits



Durability

- High-quality coating extends the life of the glove and provides excellent protection for the hand



Easy to use

- Perfect fit so that users do not feel any discomfort in the wrist area with prolonged use



Hygiene

- Reduces perspiration thanks to its excellent breathability



Performance

- Flexible reinforcements for added protection against impact and pinching
- SOFTnocut fiber provides excellent cut resistance

Applications

- Agriculture
- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive

Certifications and norms



EN 388
3 X 4 2 D P



EN 407
X 2 X X X X

Protects against risks



Heat



Shock



Cutting



Wearing



Hand protection

EOS FLEX CUT D VV922

LONG-LASTING CUT WORK

Impact-resistant glove with level D cut protection for the whole hand, ideal for multi-purpose work in aqueous or oily environments

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997
P [P] IMPACT RESISTANCE (OPTIONAL)



EN 407

X [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Impact-resistant glove
Tight glove kind	Unsupported
Mechanical glove kind	Knitted
Special gloves kind	Impact
Weft yarn	SOFTnocut (Mixed HDPE /Spandex / polyamide)
Coating level	Fully coated
Coating material	Thermoplastic
Coating finition	Smooth
Number of layer	Single layer
Gauge	15
Color	Black
Size	9
Type of packaging	Header card

Packaging

Sale unit: Header card
60 pairs /box



Safety gloves

EOS FLEX CUT D VV922

LONG-LASTING CUT WORK

Impact-resistant glove with level D cut protection for the whole hand, ideal for multi-purpose work in aqueous or oily environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
GOI922KH01BK09 [VV922NO09]	Black	09	EOS FLEX CUT D VV922	3295249268640	13295249268647	60	6	18.52 kg	73.5 cm	28.5 cm	36.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height