



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers



Specific benefits



Comfort

- 3D comfort foam integrated into harnesses, providing comfort and breathability for extended use
- Thermoformed belt for optimal lumbar support and comfort



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 150 kg



Easy to use

- Ergonomic design facilitating user movements
- NFC system guarantees traceability

Applications

- Public works
- Finishing works / Craftsmanship
- Chemical industry
- Automotive
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN361
150 KG

EN813
150 KG

EN358

Protects against risks



Fall



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Standards - Details

Technical details

Type of equipment	Fall arrest, support and suspension harnesses
Composition of the main support	Aluminum, Polyester
Fastening	Buckles
Number of attachment points	2
Number of total suspension points	1
Number of total holding attachment points	2
Anti-fall point	Dorsal, Sternal
Suspension point	Ventral
Holding point	Belt
Color	Grey-Yellow
Comfort elements	"Soft padding" on shoulders and thigh strap, Thermocompressed back and shorts
Size	XS, S/M/L, XL/XXL
Benefits element	Comfort, Fall indicator
Number of non-removable buckles	4
Weight (kg)	2,5
Number of manual buckles	2
Number of automatic loops	2
Number of fall arrest anchorage points	2
Padding	Back, Belt, Leg
Sternal	1
Dorsal	1
Belt	1
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space,

	than 3 m), Long movement with multi connection /disconnection
--	---



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
HARLYN02S01G RSM [HAR35RPT]	Grey-Yellow	S	LYNX HAR35R	3295249270216	13295249270213	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HARLYN02S01G RML [HAR35RGT]	Grey-Yellow	M/L	LYNX HAR35R	3295249265304	13295249265301	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm
HARLYN02S01G R2X [HAR35RXX]	Grey-Yellow	XL/XXL	LYNX HAR35R	3295249265311	13295249265318	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height