



Fall protection

SPIRAL AN208S200AD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges



Durability

- Thermo-retractable tube to extend the life of lanyards

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Power Energy
- Storage

Protects against risks



Fall



Fall protection

SPIRAL AN208S200AD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances

Standards - Details

Technical details

Type of equipment	Energy-absorbing lanyard made of braided rope with thermoformable sheath
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Rope diameter (mm)	10,5
With connector	yes
Color	White-Black
Connector (user side)	Automatic lock hook, steel, opening 19mm
Benefits element	Leading edge
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Weight (kg)	1,27
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616



Fall protection

SPIRAL AN208S200AD

ENERGY ABSORBING LANYARDS

Compact, energy-absorbing lanyard with patented system guaranteeing freedom of movement for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS6002DZ011 [AN208S200AD]	White-Black	2 m	SPIRAL AN208S200AD	3295249265069	13295249265066	5	1	7.41 kg	29.5 cm	45.5 cm	17.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height