Fall protection

AN513180JWW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Specific benefits

Hygiene

· Harnesses and textiles can be washed with neutral soap

Easy to use

· NFC system guarantees traceability

Durability

· High webbing tenacity thanks to its weave and width

Applications

- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Heavy industry**
- **Light industry**
- **Maintenance**

Certifications and norms

ANSI Z359.13-2013 (R2022)

CSA Z259.11-17

Protects against risks

Fall

Fall protection

AN513180JWW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Galvanized steel, Polyester
Length (m)	1.8
With connector	yes
Color	Black-Yellow
Connector (user side)	Small hook, steel, opening 21 mm
Ending	3 sewn thimble loops
Connector (structure side)	2 automatic lock hook, steel, opening 65 mm
Lifespan from manufacturing (years)	10
Weight (kg)	2.6
Type of packaging	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	5.9055

Fall protection

AN513180JWW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height