Fall protection

AN213200ZZZ

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Specific benefits

Hygiene

· Harnesses and textiles can be washed with neutral soap

Performance

· Strap with improved abrasion resistance and certified for use on sharp edges

· Certification above the maximum rated load of 100 kg: product certified at 140 kg

Applications

- **Public works**
- **Finishing works / Craftsmanship**
- **Automotive**
- **Power Energy**
- **Storage**

Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Protects against risks

Fall

Fall protection

AN213200ZZZ

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	Crochet à verrouillage automatique, acier, ouverture 19 mm
Lifespan from manufacturing (years)	10
Weight (kg)	0,668
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616

AN213200ZZZ

ENERGY ABSORBING LANYARDS

Fall protection

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
ENAD1002ZZ011 [AN213200ZZZ]	Orange	2 m	AN213200ZZZ	3295249265090	13295249265097	5	1	5.63 kg	22.0 cm	31.0 cm	16.0 cm

Multiple Sales

Minimum Order Quantity

Box Width

Box Depth

Box Height