



Fall protection

FENNEC AN06330

FALL ARRESTERS ON ROPE

Sliding fall arrest system already mounted on its rope which makes it easy to set it up for occasional users over a length of 30 metres



Specific benefits



Easy to use

- NFC system guarantees traceability

Applications

- Building
- Finishing works / Craftsmanship
- Maintenance

Certifications and norms



EN353-2

100 KG | MAXIMUM RATED LOAD: 100

Protects against risks



Fall



Fall protection

FENNEC AN06330

FALL ARRESTERS ON ROPE

Sliding fall arrest system already mounted on its rope which makes it easy to set it up for occasional users over a length of 30 metres

Standards - Details

Technical details

Type of equipment	Guided fall arrester for rope
Composition of the main support	Steel, Stainless steel, Polyamide
Max. length (m)	30
Length (m)	30
Rope diameter (mm)	12,7
Included elements	Wear indicator
Color	White-Black
Ending	1 loop spliced on high end
Weight (kg)	3,4
Fall arrest work situations	Movement on lifeline, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Long horizontal movement on horizontal surface
Maximum rated load (kg)	100
Lenght (ft)	98.4241
Type of opening	Non-opening



Fall protection

FENNEC AN06330

FALL ARRESTERS ON ROPE

Sliding fall arrest system already mounted on its rope which makes it easy to set it up for occasional users over a length of 30 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
-----------	--------	------	-------------	-------	----------	---	---	--------	---	---	---

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height